



Roller length (mm):	1880
Roller diameter (mm):	330
Heating	Electric
Hourly production (Kg/h)	40
Ironing speed (mt/min):	1-6
Voltage	3x400V+N 50Hz
Heating power (Kw):	25,2
Machine dimension (WxDxH - mm):	2514X598X1072
Net weight (Kg):	488
Packing dimension (WxDxH - mm):	2610X710X1270
Gross weight (Kg):	520

- ☑ Frontal linen entry and exit, the ironer can be installed against a wall.
- ☑ Introducing and ironing belts in NOXEM, high temperature resistant.
- ☑ Hand safe bar.
- ☑ Two emergency stop button, one on each side, to stop immediately the ironer in case of it is needed.
- ☑ New IM7 microprocessor: easy and intuitive to be used, it allows to create, label and save up to 30 ironing programs. Information referring to the operation in execution and to the ironer works appear on the big display.
- ☑ Ironing temperature and speed electronic control.
- ☑ Automatic compensation of the ironing speed in function of the ironing temperature: when the chest temperature decrease because of the linen humidity, the ironing speed is automatically and proportionally decrease in order to assure the optimal mix of the two parameter and the highest ironing quality.
- ☑ Big tray to lay the linen to be introduced in the ironer.
- ☑ Big tray to collect the ironed linen.



Note: technical data and characteristics may be changed without any previous notice.



Roller length (mm):	1880
Roller diameter (mm):	330
Heating	Gas
Hourly production (Kg/h)	40
Ironing speed (mt/min):	1-6
Voltage	3x400V+N 50Hz
Heating power (Kw):	24,6
Machine dimension (WxDxH - mm):	2514X598X1072
Net weight (Kg):	488
Packing dimension (WxDxH - mm):	2610X710X1270
Gross weight (Kg):	520

- ☑ Frontal linen entry and exit, the ironer can be installed against a wall.
- ☑ Introducing and ironing belts in NOXEM, high temperature resistant.
- ☑ Hand safe bar.
- ☑ Two emergency stop button, one on each side, to stop immediately the ironer in case of it is needed.
- ☑ New IM7 microprocessor: easy and intuitive to be used, it allows to create, label and save up to 30 ironing programs. Information referring to the operation in execution and to the ironer works appear on the big display.
- ☑ Ironing temperature and speed electronic control.
- ☑ Automatic compensation of the ironing speed in function of the ironing temperature: when the chest temperature decrease because of the linen humidity, the ironing speed is automatically and proportionally decrease in order to assure the optimal mix of the two parameter and the highest ironing quality.
- ☑ Big tray to lay the linen to be introduced in the ironer.
- ☑ Big tray to collect the ironed linen.



Note: technical data and characteristics may be changed without any previous notice.