



Roller length (mm): 2717
Roller diameter (mm): 502
Heating Electric
Hourly production (Kg/h) 68
Ironing speed (mt/min): 1-9

Voltage 3x400V+N 50Hz

Heating power (Kw): 52,2

Machine dimension (WxDxH - mm): 3610X1026X1678

Net weight (Kg): 1268

Packing dimension (WxDxH - mm): 3622X1100X1868

Gross weight (Kg): 1378

- Frontal linen entry and exit, the ironer can be installed against a wall.
- Introducing and ironing belts in NOXEM, high temperature resistant.
- Hand safe bar.
- Two emergency stop button, one on each side, to stop immediately the ironer in case of it is needed.
- New IM7 microprocessor: easy and intuitive to be used, it allows to create, label and save up to 30 ironing programs. Information referring to the operation in execution and to the ironer works appear on the big display.
- Ironing temperature and speed electronic control.
- Automatic compensation of the ironing speed in function of the ironing temperature: when the chest temperature decrease because of the linen humidity, the ironing speed is automatically and proportionally decrease in order to assure the optimal mix of the two parameter and the highest ironing quality.
- Big tray to lay the linen to be introduced in the ironer.
- Big tray to collect the ironed linen.

 ϵ



Note: technical data and characteristics may be changed without any previous notice.







Roller length (mm): 2717
Roller diameter (mm): 502
Heating Gas
Hourly production (Kg/h) 68
Ironing speed (mt/min): 1-9

Voltage 3x400V+N 50Hz

Heating power (Kw): 57

Machine dimension (WxDxH - mm): 3610X1026X1678

Net weight (Kg): 1268

Packing dimension (WxDxH - mm): 3622X1100X1868

Gross weight (Kg): 1378

- Frontal linen entry and exit, the ironer can be installed against a wall.
- Introducing and ironing belts in NOXEM, high temperature resistant.
- Hand safe bar.
- Two emergency stop button, one on each side, to stop immediately the ironer in case of it is needed.
- New IM7 microprocessor: easy and intuitive to be used, it allows to create, label and save up to 30 ironing programs. Information referring to the operation in execution and to the ironer works appear on the big display.
- Ironing temperature and speed electronic control.
- Automatic compensation of the ironing speed in function of the ironing temperature: when the chest temperature decrease because of the linen humidity, the ironing speed is automatically and proportionally decrease in order to assure the optimal mix of the two parameter and the highest ironing quality.
- Big tray to lay the linen to be introduced in the ironer.
- Big tray to collect the ironed linen.

 ϵ



Note: technical data and characteristics may be changed without any previous notice.







Roller length (mm): 2717

Roller diameter (mm): 502

Heating Steam

Hourly production (Kg/h) 68

Ironing speed (mt/min): 1-9

Voltage 3x400V+N 50Hz

Heating power (Kw): 110

Machine dimension (WxDxH - mm): 3610X1026X1678

Net weight (Kg): 1268

Packing dimension (WxDxH - mm): 3622X1100X1868

Gross weight (Kg): 1378

- Frontal linen entry and exit, the ironer can be installed against a wall.
- Introducing and ironing belts in NOXEM, high temperature resistant.
- Hand safe bar.
- Two emergency stop button, one on each side, to stop immediately the ironer in case of it is needed.
- New IM7 microprocessor: easy and intuitive to be used, it allows to create, label and save up to 30 ironing programs. Information referring to the operation in execution and to the ironer works appear on the big display.
- Ironing temperature and speed electronic control.
- Automatic compensation of the ironing speed in function of the ironing temperature: when the chest temperature decrease because of the linen humidity, the ironing speed is automatically and proportionally decrease in order to assure the optimal mix of the two parameter and the highest ironing quality.
- Big tray to lay the linen to be introduced in the ironer.
- Big tray to collect the ironed linen.
- Steam roller certified PED.

CE



Note: technical data and characteristics may be changed without any previous notice.

