



Roller length (mm):	3135
Roller diameter (mm):	502
Heating	Electric
Hourly production (Kg/h)	80
Ironing speed (mt/min):	1-9
Voltage	3x400V+N 50Hz
Heating power (Kw):	61,2
Machine dimension (WxDxH - mm):	4027X1026X1678
Net weight (Kg):	1523
Packing dimension (WxDxH - mm):	4040X1100X1868
Gross weight (Kg):	1643

- ☑ Frontal linen entry
- ☑ Possibility to select at any time the ironed linen exit side. When necessary the machine become a “pass-through” equipment.
- ☑ Introducing and ironing belts in NOXEM, high temperature resistant.
- ☑ Hand safe bar.
- ☑ Two emergency stop buttons, one on each side, to stop immediately the ironer in case of it is needed.
- ☑ PLC control, easy and intuitive, this system allows to create, label and save up to 128 programs. The PLC is equipped with a huge touch screen which allows the main function management, i.e. ironing temperature and speed control, fold configuration, linen exit side choice.
- ☑ Automatic compensation of the ironing speed in function of the ironing temperature: when the chest temperature decrease because of the linen humidity, the ironing speed is automatically and proportionally decrease in order to assure the optimal mix of the two parameter and the highest ironing quality.
- ☑ Possibility to work on all the roller length or on two independent lines.
- ☑ Big tray to lay the linen to be introduced in the ironer.
- ☑ Two collecting tray (one frontal the other rear) to receive the ironed linen. When not used the tray can be push against the machine to be hid.



**Note: technical data and characteristics may be changed without any previous notice.**



Roller length (mm):	3135
Roller diameter (mm):	502
Heating	Gas
Hourly production (Kg/h)	80
Ironing speed (mt/min):	1-9
Voltage	3x400V+N 50Hz
Heating power (Kw):	68
Machine dimension (WxDxH - mm):	4027X1026X1678
Net weight (Kg):	1523
Packing dimension (WxDxH - mm):	4040X1100X1868
Gross weight (Kg):	1643

- ☑ Frontal linen entry
- ☑ Possibility to select at any time the ironed linen exit side. When necessary the machine become a “pass-through” equipment.
- ☑ Introducing and ironing belts in NOXEM, high temperature resistant.
- ☑ Hand safe bar.
- ☑ Two emergency stop buttons, one on each side, to stop immediately the ironer in case of it is needed.
- ☑ PLC control, easy and intuitive, this system allows to create, label and save up to 128 programs. The PLC is equipped with a huge touch screen which allows the main function management, i.e. ironing temperature and speed control, fold configuration, linen exit side choice.
- ☑ Automatic compensation of the ironing speed in function of the ironing temperature: when the chest temperature decrease because of the linen humidity, the ironing speed is automatically and proportionally decrease in order to assure the optimal mix of the two parameter and the highest ironing quality.
- ☑ Possibility to work on all the roller length or on two independent lines.
- ☑ Big tray to lay the linen to be introduced in the ironer.
- ☑ Two collecting tray (one frontal the other rear) to receive the ironed linen. When not used the tray can be push against the machine to be hid.



**Note: technical data and characteristics may be changed without any previous notice.**



Roller length (mm):	3135
Roller diameter (mm):	502
Heating	Steam
Hourly production (Kg/h)	80
Ironing speed (mt/min):	1-9
Voltage	3x400V+N 50Hz
Steam consumption (Kg/h):	125
Machine dimension (WxDxH - mm):	4027X1026X1678
Net weight (Kg):	1523
Packing dimension (WxDxH - mm):	4040X1100X1868
Gross weight (Kg):	1643

- ☑ Frontal linen entry
- ☑ Possibility to select at any time the ironed linen exit side. When necessary the machine become a “pass-through” equipment.
- ☑ Introducing and ironing belts in NOXEM, high temperature resistant.
- ☑ Hand safe bar.
- ☑ Two emergency stop buttons, one on each side, to stop immediately the ironer in case of it is needed.
- ☑ PLC control, easy and intuitive, this system allows to create, label and save up to 128 programs. The PLC is equipped with a huge touch screen which allows the main function management, i.e. ironing temperature and speed control, fold configuration, linen exit side choice.
- ☑ Automatic compensation of the ironing speed in function of the ironing temperature: when the chest temperature decrease because of the linen humidity, the ironing speed is automatically and proportionally decrease in order to assure the optimal mix of the two parameter and the highest ironing quality.
- ☑ Possibility to work on all the roller length or on two independent lines.
- ☑ Big tray to lay the linen to be introduced in the ironer.
- ☑ Two collecting tray (one frontal the other rear) to receive the ironed linen. When not used the tray can be push against the machine to be hided.
- ☑ Heated cylinder certified PED.



**Note: technical data and characteristics may be changed without any previous notice.**