3x400V+N 50Hz





Loading capacity (ratio 1:10 - Europe): 8 Kg
Heating: Electric
Drum volume (It): 81
Loading diameter (mm): 282

G-Factor: 300

Machine dimension (WxDxH - mm): 720x853x1039

Net weight (Kg): 254

Packing dimension (WxDxH - mm): 760x940x1180

Gross weight (Kg): 259

- Frontal, top and side panels in stainless steel AISI 304.
- Drum and outer drum in stainless steel INOX AISI 304 (5 years warranty).

Electric supply:

- No need of ground fixing. To install the washing machine it is enough to adjust the rubber feet.
- Innovative system PBS assuring the perfect drum balance even with partial or complex loads.
- Ergonomics door locking system which reduces the user intervention: the door closing is controlled by the computer.
- Balanced water load: the washer is equipped with one hot and one cold water inlet valve. When the program is started, the washing machine load cold alternate to hot water to reach the set washing temperature in the most quicker and precise way, time of heating, and consequently the program length, is reduced.
- The modern IM8 computer is equipped with a touch screen and is able to store up to 200 programs, in the standard version, a lot more if the memory is expanded.
- Double program level standard on all washing machines:
 - 1. The EASY PROG interface allows the user to create his own program just answering to few simple questions.
 - 2. The EXPERT PROG interface allows the specialized technician to create customize programs based on the laundry needs.
- USB door on machine front for a rapid and easy data transfer between PC and washer or from a washer to the others.
- Controlled panel angled of 45° to avoid unpleasant reflex on the touch screen.
- Remote assistance by GSM standard. In case of anomalies the washing machine send an SMS to the agreed service centre, which will receive also an e-mail coming from the manufacturer server and containing a trouble shooting diagram referring to the alarm notified by the machine. The service is quicker and the solution is easier to be found.
- If necessary the machine can be equipped with automatic detergent pumps for a more precise soap measuring.









Notes: Technical data and characteristics may be changed without any previous notice.







Loading capacity (ratio 1:10 - Europe): 8 Kg

Heating: Direct Steam

Drum volume (lt): 81
Loading diameter (mm): 282
G-Factor: 300

Electric supply: 3x400V+N 50Hz

Machine dimension (WxDxH - mm): 720x853x1039

Net weight (Kg): 254

Packing dimension (WxDxH - mm): 760x940x1180

Gross weight (Kg): 259

- Frontal, top and side panels in stainless steel AISI 304.
- Drum and outer drum in stainless steel INOX AISI 304 (5 years warranty).
- No need of ground fixing. To install the washing machine it is enough to adjust the rubber feet.
- Innovative system PBS assurgi the perfect drum balance even with partial or complex loads.
- Ergonomics door locking system which reduces the user intervention: the door closing is controlled by the computer.
- Balanced water load: the washer is equipped with one hot and one cold water inlet valve. When the program is started, the washing machine load cold alternate to hot water to reach the set washing temperature in the most quicker and precise way, time of heating, and consequently the program length, is reduced.
- The modern IM8 computer is equipped with a touch screen and is able to store up to 200 programs, in the standard version, a lot more if the memory is expanded.
- Double program level standard on all washing machines:
 - 1. The EASY PROG interface allows the user to create his own program just answering to few simple questions.
 - 2. The EXPERT PROG interface allows the specialized technician to create customize programs based on the laundry needs.
- USB door on machine front for a rapid and easy data transfer between PC and washer or from a washer to the others.
- Controlled panel angled of 45° to avoid unpleasant reflex on the touch screen.
- Remote assistance by GSM standard. In case of anomalies the washing machine send an SMS to the agreed service centre, which will receive also an e-mail coming from the manufacturer server and containing a trouble shooting diagram referring to the alarm notified by the machine. The service is quicker and the solution is easier to be found.
- If necessary the machine can be equipped with automatic detergent pumps for a more precise soap measuring.










Notes: Technical data and characteristics may be changed without any previous notice.









Loading capacity (ratio 1:10 - Europe): 8 Kg

Heating: Hot water Drum volume (It): 81

Loading diameter (mm): 282 G-Factor: 300

Electric supply: 3x400V+N 50Hz

Machine dimension (WxDxH - mm): 720x853x1039

Net weight (Kg): 254

Packing dimension (WxDxH - mm): 760x940x1180

Gross weight (Kg): 259

- Frontal, top and side panels in stainless steel AISI 304.
- Drum and outer drum in stainless steel INOX AISI 304 (5 years warranty).
- No need of ground fixing. To install the washing machine it is enough to adjust the rubber feet.
- Innovative system PBS assurgi the perfect drum balance even with partial or complex loads.
- Ergonomics door locking system which reduces the user intervention: the door closing is controlled by the computer.
- Balanced water load: the washer is equipped with one hot and one cold water inlet valve. When the program is started, the washing machine load cold alternate to hot water to reach the set washing temperature in the most quicker and precise way, time of heating, and consequently the program length, is reduced.
- The modern IM8 computer is equipped with a touch screen and is able to store up to 200 programs, in the standard version, a lot more if the memory is expanded.
- Double program level standard on all washing machines:
 - 1. The EASY PROG interface allows the user to create his own program just answering to few simple questions.
 - 2. The EXPERT PROG interface allows the specialized technician to create customize programs based on the laundry needs.
- USB door on machine front for a rapid and easy data transfer between PC and washer or from a washer to the others.
- Controlled panel angled of 45° to avoid unpleasant reflex on the touch screen.
- Remote assistance by GSM standard. In case of anomalies the washing machine send an SMS to the agreed service centre, which will receive also an e-mail coming from the manufacturer server and containing a trouble shooting diagram referring to the alarm notified by the machine. The service is quicker and the solution is easier to be found.
- If necessary the machine can be equipped with automatic detergent pumps for a more precise soap measuring.









Notes: Technical data and characteristics may be changed without any previous notice.

